

<b>DKR Pressarmatur Typ RPDZ / DKR fitting type RPDZ</b>					
60° Dichtkegel mit BSP-Überwurfmutter / 60° sealing cone with BSP union nut					
Art. Nr.	Bezeichnung	Standard	DN	G1	S1
Art. N°	Description				
345.100	RPDZ 20 3/4"	•	20	3/4"	32
345.101	RPDZ 20 1"		20	1"	38
345.105	RPDZ 25 1"	•	25	1"	38
345.110	RPDZ 32 1.1/4"	•	32	1.1/4"	50
345.111	RPDZ 32 1.1/2"		32	1.1/2"	55
345.115	RPDZ 40 1.1/2"	•	40	1.1/2"	55
345.120	RPDZ 50 2"	•	50	2"	70



<b>45° DKR Pressarmatur Typ RPKZ ..J4 / DKR 45° fitting type RPKZ ..J4</b>					
60° Dichtkegel mit BSP-Überwurfmutter / 60° sealing cone with BSP union nut					
Art. Nr.	Bezeichnung	Standard	DN	G1	S1
Art. N°	Description				
345.125	RPKZ 20 3/4"/4	•	20	3/4"	32
345.130	RPKZ 25 1"/4	•	25	1"	38
345.135	RPKZ 32 1 1/4"/4	•	32	1.1/4"	50
345.140	RPKZ 40 1 1/2"/4	•	40	1.1/2"	55
345.145	RPKZ 50 2"/4	•	50	2"	70



<b>90° DKR Pressarmatur Typ RPKZ ..J9 / DKR 90° fitting type RPKZ ..J9</b>					
60° Dichtkegel mit BSP-Überwurfmutter / 60° sealing cone with BSP union nut					
Art. Nr.	Bezeichnung	Standard	DN	G1	S1
Art. N°	Description				
345.150	RPKZ 20 3/4"/9	•	20	3/4"	32
345.155	RPKZ 25 1"/9	•	25	1"	38
345.156	RPKZ 25 1 1/4"/9		25	1.1/4"	50
345.160	RPKZ 32 1 1/4"/9	•	32	1.1/4"	50
345.165	RPKZ 40 1 1/2"/9	•	40	1.1/2"	55
345.170	RPKZ 50 2"/9	•	50	2"	70



<b>AGR Pressarmatur Typ RPAZ / AGR fitting type RPAZ</b>					
BSP-Außengewinde (60° Innenkonus) / BSP male thread (60° inside cone)					
Art. Nr.	Bezeichnung	Standard	DN	G1	S1
Art. N°	Description				
345.175	RPAZ 20 3/4"	•	20	3/4"	32
345.176	RPAZ 20 1"		20	1"	41
345.180	RPAZ 25 1"	•	25	1"	41
345.181	RPAZ 25 1 1/4"		25	1.1/4"	50
345.185	RPAZ 32 1 1/4"	•	32	1.1/4"	50
345.190	RPAZ 40 1 1/2"	•	40	1.1/2"	55
345.195	RPAZ 50 2"	•	50	2"	70



**Standard** Standardgröße / Standard size  
**DN** Durchmesser Nominal / Diameter nominal  
**G1** Gewinde / Thread  
**DKO** Dichtkopf mit O-Ring / Sealing cone with O-Ring  
**R1** Rohrgröße / Pipe size  
**S1** Schlüsselweite / Hexagon