





Kupplungsstecker BG1 Typ SK1..-S / Screw on couplings male type SK1..-S				
Baugröße 1. Betriebsdruck: max. 450 bar / Size 1				
Art. Nr.	Bezeichnung	R1	G1	
Art. N°	Description			
289.110	SK1-IG G1/4"-S	-	IG G1/4"	
289.120	SK1-06L-S	L06	M12x1,5	
289.121	SK1-08L-S	L08	M14x1,5	
289.122	SK1-10L-S	L10	M16x1,5	
289.130	SK1-08S-S	S08	M16x1,5	
289.131	SK1-10S-S	S10	M18x1,5	



Kupplungsmuffe BG1 Typ SK1..-M / Screw on couplings female type SK1..-M				
Baugröße 1. Betriebsdruck: max. 450 bar / Size 1				
Art. Nr.	Bezeichnung	R1	G1	G2
Art. N°	Description			
289.010	SK1-IG G1/4" -M	-	IG G1/4"	M24x2
289.020	SK1-06L-M	L06	M12x1,5	M24x2
289.021	SK1-08L-M	L08	M14x1,5	M24x2
289.022	SK1-10L-M	L10	M16x1,5	M24x2
289.030	SK1-08S-M	S08	M16x1,5	M24x2
289.031	SK1-10S-M	S10	M18x1,5	M24x2



Schottadapter / Einschraubstutzen
Bulkhead adapter / male stud coupling
Seite / page 139 - 141